

Amendments to the Specification:

In the Title: Please replace the title "PROBE STATION" with --PROBE STATION WITH TWO PLATENS--.

On page 8,

line 3, after "supports₁" change "112a, 112b, 112c, and 112d" to read: --112A, 112B, 112C, and 112D--.

On page 11,

line 2, after the first and second occurrences of "supports₁" change "212a-212d" to read --212A-212D--;

line 3, after "openings₁" "change 220a-220d" to read --220A-220D--;

line 4, after "supports₁" change "224a-224d" to read --224A-224D--;

line 5, after the first occurrence of "supports₁" change "224a-224d" to read --224A-224D--; and after the second occurrence of "supports₁" change "212a-212d" to read --212A-212D--.

On page 13,

line 4, after "supports₁" change "350a-350d" to read --350A-350D--;

line 5, after the first occurrence of "contacts₁" change "352a-352d" to read --352A-352D--; and after the second occurrence of "contacts₁" change "352a-352d" to read --352A-352D--;

line 8, after "supports₁" change "350a-350d" to read --350A-350D--;

line 10, after "supports₁" change "350a-350d" to read --350A-350D--;

lines 11-12, after "supports₁" change "350a-350d" to read --350A-350D--;

line 14, after the first occurrence of "supports₁" change "350a-350d" to read --350A-350D--; and after the second occurrence of "supports₁" change "350a-350d" to read --350A-350D--;

line 15, after "supports₁" change "350a-350d" to read --350A-350D--;

line 16, after "mechanism" change "358" to read --359--;

line 17, after "supports₁" change "350a-350d" to read --350A-350D--; and

line 21, after "supports₁" change "350a-350d" to read --350A-350D--.